



# TUV T8

## TUV 25W 1SL/25

TUV T8 lamps are double-ended UVC (germicidal) lamps used in professional water and air disinfection units. TUV T8 lamps offer constant UV output over their complete lifetime, for maximum security of disinfection and high system efficacy. Moreover, they have a long and reliable lifetime, which allows maintenance to be planned for in advance.

### Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.
- DANGER: Risk Group 3 Ultra Violet product. These lamps emit high-power UV radiation that can cause severe injury to skin and eyes. Avoid eye and skin exposure to unshielded product. Use only in an enclosed environment which shields users from the radiation.

### Product data

General Information	
Cap base	G13 [Medium Bi-Pin Fluorescent]
Useful life (nom.)	9,000 h
Light Technical	
Colour Code	TUV
Colour designation	- [Not Specified]
Depreciation at useful lifetime	15 %
Operating and Electrical	
Power Consumption	25 W
Lamp current (nom.)	0.612 A
Voltage (nom.)	48 V


Voltage (nom.)	48 V
Mechanical and Housing	
Bulb shape	T26 [T 26 mm]
Approval and Application	
Mercury (Hg) content (nom.)	2.0 mg
UV	
UV-C Radiation at 100 hr	7.3 W
Product Data	
Order product name	TUV 25W 1SL/25
Full product name	TUV 25W 1SL/25

# TUV T8

Full EOC	871150064161840
Order code	64161840
Material no. (12 NC)	928039404005
Local order code	25TUV
SAP numerator – quantity per pack	1


EAN/UPC – Product/Case	8711500641618
Numerator – packs per outer box	25
EAN/UPC – Case	8711500641625

## Dimensional drawing



Product	D (max)	A (max)	B (max)	B (min)	C (max)
TUV 25W 1SL/25	28 mm	437.4 mm	444.5 mm	442.1 mm	451.6 mm

## Photometric data



Spectral Power Distribution Colour – TUV 25W 1SL/25

